

MINK4™ Microphone Cables

24AWG Quad-Star Low-EMI Design



- Extra-Flexible PVC Jacket
- Low-Noise, High CMNR
- 24 AWG Stranded Bare Copper
- Four Conductors - Quad Star
- Polyethylene Dielectric
- 95% TC Braid Shield
- Terminated with Neutrik Connectors

Part Number: **X - MINK4 - (length) - 0 - (connectors side 1) - (connectors side 2)**

Description: **24AWG 4 Conductor MINK4 Microphone Cable Assembly**

Options: **Length:** Given in Feet

Connector Options:

- XF = Female XLR - Neutrik, Nickel (NC3FXX)
- XFB = Female XLR - Neutrik, Black/Nickel (NC3FXX-BAG)
- XFBG = Female XLR - Neutrik, Black/Gold (NC3FXX-B)
- XM = Male XLR - Neutrik, Nickel (NC3MXX)
- XMB = Male XLR - Neutrik, Black/Nickel (NC3MXX-BAG)
- XMBG = Male XLR - Neutrik, Black/Gold (NC3MXX-B)
- TRS = 1/4" TRS - Neutrik, Nickel/Nickel (NP3X)
- TRSB = 1/4" TRS - Neutrik, Black/Nickel (NP3X-BAG)
- TRSBG = 1/4" TRS - Neutrik, Black/Gold (NP3X-B)
- TS = 1/4" TS - Neutrik, Nickel/Nickel (NP2X)
- TSB = 1/4" TS - Neutrik, Black/Nickel (NP2X-BAG)
- TSBG = 1/4" TS - Neutrik, Black/Gold (NP2X-B)

Components

Cable Type	Clark MINK4 Microphone Cable 24AWG (41x40) Stranded BC .015" Polyethylene Insulation (blue & light blue, white & yellow) 95% TC Braid with 24AWG (7x32) Stranded TC Drain Extra-Flexible PVC Jacket .236" Overall Diameter	Overall Jacket: Black
Connector Type	Neutrik XX series XLR, Neutrik NP3X series TRS, Neutrik NP2X series TS	Connector Finish: Varies

Performance Characteristics

DC Resistance	Capacitance	Temperature Range	Weight
Conductor: 25.4 Ω/Mft Shield w/ Drain: 5.2 Ω/Mft	39 pF/ft between conductors 57 pF/ft between one conductor and other in common with shield	-35 °C to 75°C	41 lbs/Mft

See MINK4 cable specifications for additional information and performance characteristics.